

Improving Sustainability in the Transport Sector



- A study by the Institute for Energy and Environmental Research (IFEU) in Heidelberg, concludes that lightweighting passenger cars, trucks, rail vehicles, nautical vessels and aircraft would have a significant impact on global, transportation-related GHG emissions.



As a general indicator...



1 kg of aluminium replacing conventional vehicle materials

has the potential to eliminate



20 kg of CO₂ during the operating life of the average vehicle



Improving Sustainability in the Transport Sector



- Measures to reduce energy consumption should concentrate on the in-use stage
 - The in-use stage of the average vehicle's life cycle represents more than 80% of total energy consumption
 - Whereas the material production, manufacturing and end-of-life stages represent less than 20%



Improving Sustainability in the Transport Sector



- Life cycle example 1: Bumper
 - The bumpers of two similar European cars were compared
 - Similar vehicle weight (1,100 to 1,200 kg)
 - Similar diesel consumption of 6 litres per 100 km
 - Same crash testing requirements



Improving Sustainability in the Transport Sector



- Life cycle example 1: Bumper
 - Bumper specifics:
 - Mass of aluminium bumper: 3.2 kg
 - Mass of high strength steel bumper: 5.8 kg
 - The aluminium solution gives 45% direct weight savings
 - No indirect saving included in this example
 - Total recycling rate 91% for both bumpers



Improving Sustainability in the Transport Sector



- Life cycle example 1: Bumper
 - The full life cycle of both solutions were compared, including the full production chain, use and recycling.
 - Utilizing public available information on production, usage and recycling.
 - Observing the methodology of life cycle assessment per ISO standard 14044 with regards to energy and greenhouse gas emissions.



Improving Sustainability in the Transport Sector




- Life cycle example 1: Bumper
 - With a lifetime of 200,000 km the aluminium bumper saves
 - 48 kg greenhouse gas emissions compared to the equivalent high strength steel bumper.
 - Or 15 kg CO₂eq per kg aluminium
 - Carbon footprint
 - Aluminium bumper: 67 kg CO₂eq
 - Steel bumper: 115 kg CO₂eq



Improving Sustainability in the Transport Sector



- Life cycle example 2: Motor block
 - This medium weight compact car has a mass of 1,250 kg and a gasoline consumption of 7.5 litres per 100 km.
 - The car manufacturer has studied an aluminium version and a steel version with identical performance characteristics
 - Mass of aluminium component: 16.4 kg
 - Mass of steel component: 31.0 kg
 - Mass difference: 14.6 kg
 - Indirect mass savings: 23% of 14.6 kg = 3.4 kg
 - Effective weight savings: 18.0 kg



Improving Sustainability in the Transport Sector



- Life cycle example 2: Motor block
 - Results for this compact car show, after a lifetime driving distance of 200,000 km, savings
 - of approximately 280 MJ per kg of aluminium in primary energy and
 - about 20 CO₂eq per kg of aluminium in greenhouse gas.



Improving Sustainability in the Transport Sector



- The use of 7 million tonnes of aluminium for passenger car components manufactured in 2006, instead of heavier materials, will result in potential global savings of:
 - approximately 140 million tonnes of CO₂ equivalent greenhouse gas emissions
 - primary energy equivalent to around 55 billion litres of crude oil

Improving Sustainability in the Transport Sector



- Aluminium industry will:
 - Continue to reduce greenhouse gas emissions from its production facilities
- Transport design should:
 - Optimise vehicle recycling
 - Aluminium scrap is recyclable, has a high value and low energy needs during the recycling process
 - Optimise energy inputs in manufacture and use

Improving Sustainability in the Transport Sector



- Full report available on IAI website
 - www.world-aluminium.org
- Model and case studies available on request
 - IAI@world-aluminium.org
- IFEU reports
 - H. Helms, U. Lambrecht and U. Höpfner: Energy savings by light-weighting, IFEU (2003) www.world-aluminium.org
 - H. Helms and U. Lambrecht: Energy savings by light-weighting, part II IFEU (2004) www.world-aluminium.org
 - H. Helms and U. Lambrecht: The Potential Contribution of Light-Weighting to Reduce Transport Energy Consumption. Int. J. LCA 12 (2) 140 (2007), pp. 58–64